DAIHAN-brand[®] Vertical Clean Bench and Filtered PCR Cabinet, "MaXtream™", Class 100 HEPA filter with 8 Steps Air Velocity Control, Touch-type Controller, Dual UV Lamp and Florescent Lamp, Air and Gas Cock, Built-in Electrical Outlet **크린벤치 & PCR케비넷, 수직 기류형, 터치식 컨트롤러, 8 단계 풍속 조절, UV 프로텍션 시스템**



Vertical Clean Bench and Filtered PCR Cabinet "MaXtream™ V12"



Vertical Air Flow of "MaXtream™ V model"



High-performance Digital Touch-type Controller, Easy to Use

- Made in Korea CE Certified PL(Product Liability) Insurance
- with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- Class 100 HEPA Filter of efficiency up to 99.97% & 0.3 micron size
- Mesh Guard for HEPA Filter Protection
- Easy to Exchange HEPA Filter 8 Steps Air Velocity Control ■ Safety UV Protection System :
- UV Lamp is only activated once safety Glass Door is Completely closed ■ High performance of Touch Controller-Easy to use
- Microprocessor Digital Controller and Back Light LCD
- UV and Fluorescent Lamp, External Gas Connection Valve, Internal Electrical outlet
- * High-Quality Back-Light LCD * 99hr 59min Timer
- * Silence and Vibration-Free Blower
- * Tempered Safety Glass Sliding Door for Protection from Against UV
- * Optimized Air Flow System for Uniform Air Flow/Velocity
- * Corrosion Resistant 304 Stainless-steel Working table
- * Air Flow-type : Vertical Air Flow-type

Specifications & Ordering information

Spec. Model		"MaXtream™ V12"	"MaXtream™ V15"	"MaXtream™ V18"
Air Flow-type		Vertical Air Flow-type		
Dimension (w×d×h)	Interior	1,200×660×610	1,500×660×610	1,800×660×610
	Exterior	1,280×735×1,895	1,580×735×1,895	1,880×735×1,895
Air Volume		1,350 m²/h	1,700 m²/h	2,020 m²/h
Air Flow Velocity		8 Steps, 0.3 ~ 0.6 m/s		
HEPA Filter		Class 100, 0.3µm Particle Removal 99.97%		
Prefilter		3~30µm Particle Removal		
Display		Back Light LCD		
Controller		Microprocessor Digital Controller with Touch UI		
Lamp		1×UV 20W, 1×FL 36W 1×UV 30W, 1×FL 55W		
Noise Level		Under 65dBA		
Door Type		Tempered Safety Glass Sliding Door		
Utility Device		1×Air Cock, 1×Gas Cock, 2×220V Outlet		
Material		Internal : Stainless-steel(# 304), External : Powder Coated steel		
Electric Reqts.		1 Phase, AC 120 V, 60 Hz or AC 230 V, 50 / 60 Hz		
Cat. No.	230V	DH.WLCV1200	DH.WLCV1500	DH.WLCV1800
	120V	DH.WLCV1201	DH.WLCV1501	DH.WLCV1801
Price, Each. ₩		4,297,000	4,527,000	4,683,000
* Other Specifications are available upon Customer's Request. ※ 유임 약 ₩ 95.000 별도				

on Customer's Request. ※ 운임 약 ₩ 95,000 멀노!